



Rated operational current		Actuating voltage	Actuating current	Contact sequence	For use with	Part no. Article no.	Price see price list	Std. pack
AC-15	DC							
240 V	415 V							
I_e	I_e	I_e	U_s	I				
A	A	A	V DC	mA				

Amplifier module for separate mounting

Input with integrated suppressor for overvoltage limit

2	2	0.03	24	25	As required	ETS4-VS3 083094		1 off
---	---	------	----	----	-------------	---------------------------	--	-------




Notes

Contactors coils with rated operational current > 2 A must be actuated via the DILA mini contactor relay.
Rated operational current DC:
Making and breaking conditions DC-13, time L/R 300ms




For use with	AC Part no. Article no.	Price see price list	DC Part no. Article no.	Price see price list	Std. pack	Notes
--------------	-------------------------	----------------------	-------------------------	----------------------	-----------	-------

Individual coils



DILM17 DILM25 DILM32	DILM32-XSP(230V50HZ) 281141		DILM32-XSP(RDC24)¹⁾ 281155		1 off	Other actuating voltages → 5/57
DILM40 DILM50 DILM65 DILM72	DILM65-XSP(230V50HZ) 281171		DILM65-XSP(RDC24)¹⁾ 281185			Further actuating voltages * 281130 Manufactured from KW 27/2006
DILM80 DILM95	DILM95-XSP(230V50HZ) 230062		DILM95-XSP(RDC24)¹⁾ 230080			
DILM115 DILM150 DILM170	DILM150-XSP(RAC240)¹⁾ 230112		DILM150-XSP(RDC24)¹⁾ 230115			

Electronic modules including coils



DILM185 DILM225 DILM250	DILM250-XSP/E(RA250) 208252		DILM250-XSP/E(RA250) 208252		1 off	Further actuating voltages → 5/59
DILM300 DILM400 DILM500	DILM500-XSP/E(RA250) 208256		DILM500-XSP/E(RA250) 208256			
DILM580 DILM650 DILM750 DILM820 DILM1000	DILM1000-XSP/E(RA250) 289145		DILM1000-XSP/E(RA250) 289145			
DILH1400	DILH1400-XSP/E(RAW250) 289161					
DILM185-S DILM225-S DILM250-S	DILM250-S-XSP/E(220-240V50/60HZ) 274202					
DILM300-S DILM400-S DILM500-S	DILM500-S-XSP/E(220-240V50/60HZ) 274205					

Notes

¹⁾ Including electronics module