

P1DIL...M, DILM...-XP1

Moeller HPL0211-2007/2008

<http://catalog.moeller.net>

			P1DILEM DILM12-XP1	DILM32-XP1	DILM65-XP1	DILM150-XP1	DILM185-XP1
Parallel link							
Terminal capacities							
Solid		mm ²	1 – 16	16	16	–	–
Flexible with ferrule		mm ²	1 × (0.5 – 25) 2 × (0.5 – 16)	1 × (16 – 35)	1 × (16 – 120)	–	–
Stranded		mm ²	1 × (0.5 – 25) 2 × (0.5 – 16)	1 × (16 – 50)	1 × (16 – 120)	1 × (35 – 300) 2 × (35 – 120)	–
Flat conductor	Number of segments × width × thickness	mm	6 × 9 × 0.8			2 × (11 × 21 × 1)	1 × (6 × 16 × 0.8) 2 × (20 × 32 × 0.5) 2 × (11 × 21 × 1)
Tightening torque		Nm	4	4	14	–	6
Terminal capacity control circuit cables							
Solid		mm ²	–	–	–	–	1 × (0.75 – 4) 2 × (0.75 – 4)
Flexible with ferrule		mm ²	–	–	–	–	1 × (0.75 – 2.5) 2 × (0.75 – 2.5)
Tool							
Pozidriv screwdriver		Size	2	2	–	–	–
Hexagon socket-head spanner	SW	mm	–	–	5	6	5
Conventional thermal current							
3-pole	I_{th}	A	50	100	180	400	700
4-pole	I_{th}	A	60	–	–	–	–

