


| 1 | 2 | 3 | | | | 4 | 5 |
|---|---------------------------|-----------------------------|----------|------------|----------|--------------------|----------------------------------|
| Frame Rating | Continuous Current Rating | Maximum HP Rating 3 Phase @ | | | | Type | Price |
| | Amps | 200 V HP | 230 V HP | 460 V HP | 575 V HP | | \$ |
| N9-...-CNA Motor Disconnect Switches | | | | | | N 9-250-CNA | See Price List See Price List |
|  (250A) | 250 | 60 | 75 | 150 | 200 | | |

Type **N9...-CNA** Disconnect Switches are UL recognized (UL 508) and CSA certified (22.2 Nr. 14) as 3 pole, HP rated nonautomatic manual motor disconnects without any overload or short circuit tripping elements. Their switching mechanism has 3 positions (OFF, ON, + "Tripped") and they can be equipped with voltage trip accessories such as shunt trip and undervoltage trip coils.
UL/CSA Short Circuit Rating @ 600 V AC: 10 kA RMS Sym.

N9...-CNA Disconnect Switches are also CE Marked and in Conformity with IEC/EN 60 947-3 (Switch-Disconnectors), which makes them suitable internationally as Main Disconnect switches in a broad range of industrial applications. Consult the technical data at the back of this section and Moeller Electric for IEC/EN ratings.

Ordering Information:
State type from Column 5: **N 9-250-CNA**

- Note:
- For direct-on-line switching of motors, use in combination with a listed magnetic contactor.
 - Operating Handle supplied separately. Consult page 8/28 for available handle types.
 - Consult page 8/ 26 - 31 for additional accessories.
 - Line and Load field-wiring terminals for cable connection supplied as standard.