


1	2	3				4	5
Frame Rating	Continuous Current Rating	Maximum HP Rating 3 Phase @				Type	Price
	Amps	200 V HP	230 V HP	460 V HP	575 V HP		\$
N12-...-CNA Motor Disconnect Switches							
	600	200	250	450	600	N 12-630-CNA	See Price List
	800	250	300	600	750	N 12-800-CNA	See Price List
	1000	250	300	600	750	N 12-1000-CNA	See Price List
	1200	300	450	1000	1000	N 12-1200-CNA ¹⁾	See Price List

Type **N 12...-CNA** Disconnect Switches are UL recognized (UL 508) and CSA certified (22.2 Nr. 14) as 3 pole, HP rated non-automatic manual motor disconnects without any overload or short circuit tripping elements. Their switching mechanism has 3 positions (OFF, ON, + "Tripped") and they can be equipped with voltage trip accessories such as shunt trip and undervoltage trip coils.
UL/CSA Short Circuit Rating @ 600VAC: 42 kA RMS Sym.

Ordering Information:
State type from Column 4. Example: **N 12-800-CNA**

- Note:
- For direct-on-line switching of motors, use in combination with a listed magnetic contactor.
 - Operating Handle supplied separately. Consult page 8/36 for available handle types.
 - Consult page 8/34 - 39 for additional accessories.
 - Line and Load field-wiring terminals for cable connection supplied as standard.

1) **N 12-1200-CNA** is supplied standard with bolt-on connection only. Field-wiring terminals for conductor hook-up (up to 4 x 500 kcmil, Cu or Al) can be supplied but must be ordered with the device. Add the following suffixes to the Type number.
Example: **N 12-1200-CNA**
+ **K 240AL-NZM 12-O** (for top mounted terminals, set of three)
+ **K 240AL-NZM 12-U** (for bottom mounted terminals, set of three)
See price list for adder.