





					3 switch positions I, +, 0; can be tripped remotely with shunt/undervoltage release		
					Part no. Article no.	Price see price list	Std. pack    Notes
Rated current = rated uninterrupted current							
Switching capacity							
At 480 V 60 Hz      At 600 V 60 Hz							
Response range of the short-circuit releases							
$I_n = I_u$							
A					kA      kA      A		
<b>Molded case switches</b>							
These switches are especially recommended as incoming switches for the North American market. 3 pole							
Terminals standard, terminal screws as accessories							
	63	35		1250	NS1-63-NA 102681		1 off
	100	35		1250	NS1-100-NA 102682		1 off
	125	35		1250	NS1-125-NA 102683		1 off
Terminal screws standard terminals as accessories							
	160	100	50	2500	NS2-160-NA 102684		1 off
	200	100	50	2500	NS2-200-NA 102685		
	250	100	50	2500	NS2-250-NA 102686		
	400	100	50	6600	NS3-400-NA 102687		
	600	100	50	6600	NS3-600-NA 102688		
	800	65	42	25000	NS4-800-NA <sup>1)</sup> 102689		
	1000	65	42	25000	NS4-1000-NA <sup>1)</sup> 102690		
	1200	65	35	25000	NS4-1200-NA <sup>1)</sup> 102691		

**Notes**

Notes for terminals → 10/47

N2, NS3 and N4 can also be combined with the NZM...-XR... remote operator.  
Undervoltage and shunt releases NZM...-XU, NZM...-XA and trip indicating auxiliary contacts (HIA) can be used.

<sup>1)</sup> Product available only on request.