





	Max. cable connection area	For use with	Terminal capacities Type of conductor	mm <sup>2</sup>	AWG/kcmil
<b>Control circuit terminal</b>					
	–	NZM1(-4), PN1(-4), N(S)1(-4)	Three- and four-pole	Screw connection	1 × 0.75 – 2.5 2 × 0.75 – 1.5
	–			Box terminal	1 × 18 – 14 2 × 18 – 16
<b>Cover</b>					
	–	NZM1(-4), PN1(-4), N(S)1(-4)	3 pole		
	–		4 pole		
<b>Terminal cover, knockout, not UL/CSA approved</b>					
For box terminals					
	–	NZM1, PN1, N1	3-pole		
	–	NZM1(-4), PN1(-4), N1(-4)	4 pole		
<b>IP2X protection against contact with a finger</b>					
For box terminals					
	–	NZM1, PN1, N1	3 pole		
	–	NZM1(-4), PN1(-4), N1(-4)	4 pole		
For cover NZM1(-4)-XKSA or NZM1...(C)NA, N(S)1...NA					
	–	NZM1, PN1, NS1	3 pole		
	–	NZM1(-4), PN1(-4), N1(-4)	4 pole		

Part no. Article no. when ordered separately	Std. pack	Notes
<b>NZM1-XSTS</b> 260150	1 off	Type contains parts for two terminal locations located at top or bottom for 3 or 4-pole circuit-breakers. Included as standard with tunnel terminal Degree of protection IP1X
<b>NZM-XSTK</b> 266739	1 off	NZM-XSTK cannot be combined with NZM1(-4)-XIPK IP2X protection against contact with a finger. Height or thickness of the control terminals: NZM-XSTK = 2 mm NZM-XSTS = 2 mm
<b>NZM1-XKSA</b> 260021	1 off	Type contains parts for a terminal located at top or bottom for 3 or 4-pole circuit-breakers. Protection against direct contact where cable lugs, busbars or tunnel terminals are used
<b>NZM1-4-XKSA</b> 266741	1 off	Contained in kit with tunnel terminals or screw connection terminals. Degree of protection IP1X on the connection side when using insulated conductor material.
<b>NZM1-XKSFA</b> 100780	1 off	Type contains parts for a terminal located at top or bottom for 3 or 4 pole circuit-breakers. Enhancement of the protection against direct contact (simple finger protection).
<b>NZM1-4-XKSFA</b> 100781	1 off	
<b>NZM1-XIPK</b> 266744	1 off	Type contains parts for a terminal located at top or bottom for 3 or 4-pole circuit-breakers. Enhancement of the protection against direct contact to IP2X.
<b>NZM1-4-XIPK</b> 266745	1 off	Protection when reaching into the cable connection area with the connection of cables in the box terminal. Cannot be combined with NZM-XSTK control circuit terminal.
<b>NZM1-XIPA</b> 266748	1 off	Type contains parts for a terminal located at top or bottom for 3 or 4-pole circuit-breakers. Enhancement of the protection against direct contact to IP2X.
<b>NZM1-4-XIPA</b> 266749	1 off	