


Inverse Time Circuit Breakers, 150 Amps, 480 VAC Thermal-Magnetic Type NZM 7...-NA

UL/CSA, IEC/EN 60 947-2¹⁾

| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | |
|--|---|---|--|--|---|--|--|--|
| | Continuous Current Rating | Fixed Thermal Setting | Adjustable Thermal Setting | Magnetic Trip Setting for Instantaneous Response | UL/CSA Interrupting ratings (AC, 60Hz) RMS Sym Amps @ | Type | Price | |
| | I_u Amps | Amps | Amps | Amps | 240 V 480 V | | \$ | |
| Pressure-wire terminals and fixed thermal setting | | | | | | | | |
| Type NZM 7A...N-NA | | | | | | | | |
|  (150A) | 40 | 25 30 35 40 | — — — — | Fixed: $9.5 \times I_u$ | 65 kA 25 kA | NZM 7A-25N-NA NZM 7A-30N-NA NZM 7A-35N-NA NZM 7A-40N-NA | See Price List See Price List See Price List See Price List | |
| | 60 | 50 60 70 80 90 100 125 150 | — — — — — — — — | Adjustable Range: $6 - 12 \times I_u$ | | NZM 7A-50N-NA NZM 7A-60N-NA NZM 7A-70N-NA NZM 7A-80N-NA NZM 7A-90N-NA NZM 7A-100N-NA NZM 7A-125N-NA NZM 7A-150N-NA | See Price List See Price List See Price List See Price List See Price List See Price List See Price List See Price List | |
| | Pressure-wire terminals and adjustable thermal setting | | | | | | | |
| | Type NZM 7A...N-NA | | | | | | | |
| | 40 | — | 25 – 40 | $9.5 \times I_u$ | 65 kA 25 kA | NZM 7-40N-NA | See Price List | |
| | 60 | — | 40 – 60 | $6 - 12 \times I_u$ | | NZM 7-63N-NA NZM 7-80N-NA NZM 7-100N-NA NZM 7-125N-NA NZM 7-150N-NA | See Price List See Price List See Price List See Price List See Price List | |
| | 80 | — | 60 – 80 | | | | | |
| | 100 | — | 80 – 100 | | | | | |
| | 125 | — | 100 – 125 | | | | | |
| | 150 | — | 125 – 150 | | | | | |
| Fixed thermal setting and provisions for bolt-on connection | | | | | | | | |
| Type NZM 7A...N-NA | | | | | | | | |
| 40 | 25 30 35 40 | — — — — | Fixed: $9.5 \times I_u$ | 65 kA 25 kA | NZM 7A-25N-NA-M8 NZM 7A-30N-NA-M8 NZM 7A-35N-NA-M8 NZM 7A-40N-NA-M8 | See Price List See Price List See Price List See Price List | | |
| 60 | 50 60 70 80 90 100 125 150 | — — — — — — — — | Adjustable Range: $6 - 12 \times I_u$ | | NZM 7A-50N-NA-M8 NZM 7A-60N-NA-M8 NZM 7A-70N-NA-M8 NZM 7A-80N-NA-M8 NZM 7A-90N-NA-M8 NZM 7A-100N-NA-M8 NZM 7A-125N-NA-M8 NZM 7A-150N-NA-M8 | See Price List See Price List See Price List See Price List See Price List See Price List See Price List See Price List | | |
| 80 | 70 | — | | | | | | |
| 100 | 80 | — | | | | | | |
| 125 | 90 | — | | | | | | |
| 150 | 100 | — | | | | | | |
| 125 | 125 | — | | | | | | |
| 150 | 150 | — | | | | | | |
| Adjustable thermal setting and provisions for bolt-on connection | | | | | | | | |
| Type NZM 7...N-NA | | | | | | | | |
| 40 | — | 25 – 40 | $9.5 \times I_u$ | 65 kA 25 kA | NZM 7-40N-NA-M8 | See Price List | | |
| 60 | — | 40 – 60 | $6 - 12 \times I_u$ | | NZM 7-63N-NA-M8 NZM 7-80N-NA-M8 NZM 7-100N-NA-M8 NZM 7-125N-NA-M8 NZM 7-150N-NA-M8 | See Price List See Price List See Price List See Price List See Price List | | |
| 80 | — | 60 – 80 | | | | | | |
| 100 | — | 80 – 100 | | | | | | |
| 125 | — | 100 – 125 | | | | | | |
| 150 | — | 125 – 150 | | | | | | |

Ordering Information: Specify Type from Column 7.
Example: **NZM 7A-25N-NA**.

1) Conformity with IEC/EN 60 947-2 pending. Consult the technical data at the back of this section and Moeller Electric for IEC/EN ratings.

Disconnect Switches, Molded Case Switches
Circuit Breakers

