



## L1-CI 44

6/93 AWA 461-766

Gerät, Loch-Nr. und Schraubengröße des Gerätes (M...x...); Kopfform DIN 7985; Federscheibe DIN 137 A

Devices, hole no. and size of the screws for the devices (M...x...); screwhead shape DIN 7985; spring washer DIN 137 A

Appareils, no. des trous et taille des vis pour les appareils (M...x...); forme de tête DIN 7985; rondelle élastique DIN 137 A

Typ	DIL 2 (A)M	SDAINL 2 (A)M	DIL 2-22	DIL 3-22	DIL 4-22	DIL 6-22	DIL 8-22	TC-FMO	Z 4	ZW 6	ZR 720	Dd + Kdc + BT 45l	K 25/l	K 50/l	K 95/lN	K 150/l	K 240/l	DIL 3M	SDAINL 3M	DIL 4M	
	M 5 x 16	M 5 x 12	M 5 x 20			M 4 x 16			M 5 x 20	M 4 x 8	M 4 x 16	M 5 x 9	M 5 x 12	M 6 x 16		M 5 x 12		M 5 x 12			
SDAINL 2(A)M/1		2						3				6									
DIL 3-22(Z4)/1			14					34, 35, 36	16				10								
UPIL 3-22(Z4/Z4)			15					3, 4, 5	16, 19												
SDAINL 3-22(Z4)	9		22	20, 21				3	18		32			10							
DIL 4-22/1					17									30							
DIL 4-22(Z4)/1					12			3	13												
DIL 4-22/P1/1					17										33						
DIL 4-22/G/1														10, 30							
DIL 4-22(Z4)/1					17			3, 4, 5	18					10							
SDAINL 4-22(Z4)/1			21					3			32			30							
DIL 6-22						28								10							
DIL 6-22(Z4)/1						26		3	25					30							
DIL 6-22/G/1						28										33					
DIL 6-22/P1/1						26															
DIL 6-22(Z4)/1						28		3, 4, 5	18					10, 30							
SDAINL 6-22(Z4)/1			17			26, 28		3	25		32			33							
DIL 8-22(Z4)/1								3	25												
DIL 8-22(ZW6)/1								3	25	27											
DIL 8-22/G/1																					
DIL 8-22/P1/1																					
DIL 8-22(Z...)/1								24	25	27											
SDAINL 8-22(Z...)/1			28					3	25		32										
DIL 3M/1/1								24, 29	3											41	
SDAINL 3M/1								3, 4, 5													40
DIL 4(A)M/1/1								3, 4, 5													42

Kernlochdurchmesser für  
metrisches Gewinde DIN 13

