



DILM Moeller HPL0211-2007/2008 <http://catalog.moeller.net>

<http://catalog.moeller.net> Moeller HPL0211-2007/2008 DILM

Rated operational current AC-3 380 V 400 V	Max. rating for three-phase motors, 50 – 60 Hz								Conventional free air thermal current $I_{th} = I_e$ AC-1 at 55 °C Open $I_{th} = I_e$	Contact sequence
	AC-3				AC-4					
I_e	220 V 230 V	380 V 400 V	660 V 690 V	1000 V	220 V 230 V	380 V 400 V	660 V 690 V	1000 V		
	P	P	P	P	P	P	P	P		
A		kW	kW	kW	kW	kW	kW	kW		A

Complete devices DILM

Complete devices DILM



185	55	90	175	108	41	75	127	108	337	
225	70	110	215	108	51	90	155	108	386	
250	75	132	240	108	62	110	189	108	429	
300	90	160	286	132	75	132	229	132	490	
400	125	200	344	132	92	160	283	132	612	
500	155	250	344	132	112	200	344	132	857	

Notes

660/690 V or 1000 V: not directly reversing

All contactors have a built-in suppressor circuit.

Accessories

Auxiliary contact modules → 5/30

Enclosure totally insulated

Further actuating voltages → 5/59

Can be combined with auxiliary contact	Part no. Article no.	Price see price list	Std. pack	Notes
----------------------------------------	----------------------	----------------------	-----------	-------

DILM1000-XHI...	DILM185-S/22(220-240V50/60HZ) 274185		1 off	
DILM1000-XHI...	DILM225-S/22(220-240V50/60HZ) 274187			
DILM1000-XHI...	DILM250-S/22(220-240V50/60HZ) 274190			
DILM1000-XHI...	DILM300-S/22(220-240V50/60HZ) 274193			
DILM1000-XHI...	DILM400-S/22(220-240V50/60HZ) 274196			
DILM1000-XHI...	DILM500-S/22(220-240V50/60HZ) 274199			