



Contactors – Reversing, System DIUL AC Operated

UL / CSA / IEC / CE

Magnetic Contactors
Magnetic Starters

3

1	2				3			4		5	6
Snap-on fastening to DIN rail or panel mounting	Rating data UL/CSA maximum Horsepower rating (HP) 50/60 Hz				IEC/EN 60 947 Maximum 3-phase Motor Ratings (kW) 50/60 Hz			Standard Auxiliary Contacts		Type open	Price
	3-phase				AC-3			NO	NC	Important: Add coil voltage and frequency from page 3/46 - 3/47 to end of type. See page 3/7 for more details.	\$
	200 V HP	230 V HP	460 V HP	575 V HP	220 V kW	380 V 400 V 440 V kW	660 V 690 V kW				
	2	3	5	5	2.2	4	4	2	1	DIUL EM/21/MV	See Price List
	3	3	7 1/2	10	3	5.5	-	1	1	DIUL 00AM/11/MV	See Price List
	7 1/2	7 1/2	10	15	4	7.5	-	1	1	DIUL 0M/11/MV	See Price List
	7 1/2	10	15	20	5.5	11	-	1	1	DIUL 0AM/11/MV	See Price List
	10	10	20	25	7.5	15	-	1	1	DIUL 1 M/11/MV	See Price List
	10	15	25	30	11	18.5	-	1	1	DIUL 1 AM/11/MV	See Price List
	15	20	40	40	15	22	-	1	1	DIUL 2 M/11/MV	See Price List
	20	25	50	50	18.5	30	-	1	1	DIUL 2 AM/11/MV	See Price List
	25	30	60	75	22	37	55	2	2	DIUL 3M 80/11/XMV	See Price List
	40	50	100	125	37	55	90	2	2	DIUL 4M 115/11/XMV	See Price List
	30	30	60	75	32	45	55	2	2	DIUL 3-22-V	See Price List
	40	50	100	100	55	75	90	2	2	DIUL 4-22-V	See Price List
	60	75	150	175	65	110	132	2	2	DIUL 6-22-V	See Price List
	75	100	200	250	90	160	200	2	2	DIUL 8-22-V	See Price List
	125	150	300	350	110	200	-	2	2	DIUL 8A-22-V	See Price List

Note: Reversing contactors are provided standard with a mechanical interlock and minimum 1NO and 1NC auxiliary contact per contactor (1 NC contact per contactor is normally used as an electrical interlock).

Additional Information	Page
Technical Data	3/50
Dimensions	3/61
Overload Relays	4/2
Accessories	3/35