


Accessory and Ordering Guide

DIUL 00M - DIUL 4M 115



		Page
	Auxiliary contacts	3/35
	Mechanical interlock	3/40
1.	Overload relays	4/2
	Accessories	3/35
	Technical information	3/50

For enclosed contactor information, consult Moeller Electric Corporation.

Additional Information	Page
Technical Data	3/50
Dimensions	3/61
Overload Relays	4/2
Accessories	3/35

Stock Coil Voltages	
24 V 60 Hz (through DIUL 4M 115)	
120 V 60 Hz / 110 V 50 Hz	
208 V 60 Hz	
240 V 60 Hz / 230 V 50 Hz	
480 V 60 Hz / 415 V 50 Hz	For a complete listing of standard and special coils, see page 3/46
600 V 60 Hz	

How to Order

<p>To Order Specify:</p> <p>1 Type Number</p> <p>2 Accessories</p> <p>3 Coil Voltage</p>	<p>Example: 10 HP @ 460 V AC, 3 PH reversing contactors with 1NO and 1NC standard auxiliary contacts and 120 V 60 Hz coil</p> <table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Type Number</td> <td style="text-align: center;">Coil Voltage</td> </tr> <tr> <td style="text-align: center;">DIUL 0M/11/MV</td> <td style="text-align: center;">120 V 60 Hz</td> </tr> </table>	Type Number	Coil Voltage	DIUL 0M/11/MV	120 V 60 Hz
Type Number	Coil Voltage				
DIUL 0M/11/MV	120 V 60 Hz				