

1	2	3	4
Setting range Overload release Amps		Type	Price \$
Tripping device with built-in current transformers 1.25-6.3		ZWA-6.3(110–120V 50/60Hz) ZWA-6.3(220–240V 50/60Hz) ZWA-6.3(24V DC)	See Price List See Price List See Price List
6.3-25		ZWA-25(110–120V 50/60Hz) ZWA-25(220–240V 50/60Hz) ZWA-25(24V DC)	See Price List See Price List See Price List
25-100		ZWA-100(110–120V 50/60Hz) ZWA-100(220–240V 50/60Hz) ZWA-100(24V DC)	See Price List See Price List See Price List
50-205		ZWA-205(110–120V 50/60Hz) ZWA-205(220–240V 50/60Hz) ZWA-205(24V DC)	See Price List See Price List See Price List
125-500		ZWA-500(110–120V 50/60Hz) ZWA-500(220–240V 50/60Hz) ZWA-500(24V DC)	See Price List See Price List See Price List
200-820		ZWA-820(110–120V 50/60Hz) ZWA-820(220–240V 50/60Hz) ZWA-820(24V DC)	See Price List See Price List See Price List
Current Transformers for Ground Fault protection			
Fault current Amps	Window opening for load wire		
0.3 A	40 mm (1.57 in.)	SSW40-0.3	See Price List
0.5 A		SSW40-0.5	See Price List
1 A		SSW40-1	See Price List
0.5 A	65 mm (2.55 in.)	SSW65-0.5	See Price List
1 A		SSW65-1	See Price List
0.5 A	120 mm (4.72 in.)	SSW120-0.5	See Price List
1 A		SSW120-1	See Price List